



YC Standard beam clamps

Working load limit (WLL) 1000 - 10000 kg

The YC beam clamp provides a quick and versatile rigging point for hoisting equipment, pulley blocks or loads and comes complete with a locking device. The unit offers flexible applications, due to the wide adjustment range.

The central threaded spindle allows easy attachment and a safe and secure grip to the beam flange.

Product group: C4

INFO

This model must not be used for lifting. It is only to be used as a suspension point.

Technical data YC

Model	Art.-No.	WLL kg	Beam flange width mm	Weight kg
YC1	NO5406181	1000	75 - 230	3.8
YC2	NO5406182	2000	75 - 230	4.6
YC3	NO5407417	3000	80 - 320	9.2
YC5	NO5407418	5000	90 - 320	11.0
YC10	NO5407419	10000	90 - 320	17.2

Dimensions YC

Model	YC1	YC2	YC3	YC5	YC10
A min., mm	115	115	180	180	175
A max., mm	150	150	225	225	220
A1, mm	78	78	85	95	95
A2, mm	246	246	325	325	325
B1, mm	186	186	232	242	268
B2, mm	350	350	455	445	480
b1, mm	75	75	80	90	90
b2, mm	230	230	320	320	320
C, mm	50	50	70	70	70
D, mm	3	4	6	10	14
E, mm	215	215	255	255	275
F1, mm	34	35	35	35	35
F2, mm	17	18	21	21	20
G1, mm	82	82	120	116	110
G2, mm	44	44	75	75	66
H, mm	20	20	22	28	38
J1, mm	14	14	30	30	34
J2, mm	21	21	34	34	35
K1, mm	48	50	60	60	60
K2, mm	31	32	40	42	40
L, mm	80	86	114	129	146

