

# RGHL1

## TEMPORARY LIFELINE RGHL1



The RGHL1 is a simple to install horizontal webbing safety line, incorporating a ratchet tensioner.

The RGHL1 safety line can be used in conjunction with fixed length or adjustable restraint and fall arrest lanyards. The assembly is supplied in its own bag complete with shoulder strap, enabling the user to carry it to site with little effort. Once fitted, the bag can be used for storing surplus webbing.

Kit contains

- › Horizontal safety line with ratchet tensioner
- › Anchorage sling x 2 (RGK26)
- › 24mm twistlock steel karabiner x 2 (RGK3)
- › Carry bag

(EU)2016/425

EN 362:2004

ANSI Z359.12

EN 795:2012 Type B

Material:	35mm polyester webbing line
Max. users:	2 (fall arrest) 4 (restraint)
Sizes/weights:	10m = 3kg 20m = 4kg



## ITEM SPECIFICATIONS

### RGHL1

#### HORIZONTAL SAFETY LINE WITH RATCHET TENSIONER

(EU)2016/425

Web material:	Polyester
Webbing width:	35mm (line)
Fittings:	High tensile steel alloy
Size/weight:	10m line - 3kg 20m line - 4kg
Max. Users:	2 (fall arrest) 4 (restraint)

#### ANCHORAGE SLING X 2

### RGK26

EN 795:2012 Type B

Web material:	Polyester cover and core
Breaking load:	70kN

#### 24MM TWISTLOCK STEEL KARABINER X 2

### RGK3

EN 362:2004

ANSI Z359.12

Material:	Steel
Plating:	Zinc
Gate opening:	24mm
External length:	119mm
Closure type:	Twistlock
MBS:	50kN
Weight:	300g

