

MAX.
CAPACITY
10kg



MAX.
CAPACITY
3kg

RTLK3

TWIN KINETIC® TOOL LANYARD WITH CHOKE LOOP AND BELT ATTACHMENT 'O' RING

The RTLK3 is a twin tool lanyard with a Kinetic® and a standard, both with choke loops for tool attachment and an 'O' ring on the Kinetic® for retention of a tool. The Kinetic® is suitable for tools up to 10kg in weight, the standard 3kg.

Kinetic® webbing was originally developed for our fall arrest lanyards, but works the same when used in the event of a falling tool to reduce the potentially devastating shock involved.


A Kinetic® tool lanyard significantly reduces the risk of a dropped tool dragging the user off a platform, the risk below is also reduced as its deployed distance is shorter than the shock pack version.

Web material: 25mm/20mm water repellent polyester


Length: 1.25m Kinetic
1.22m Standard

Webbing strength: >1000kg

Tool attachment: 210mm choke loop
50mm 'O' ring



Elasticated webbing



Choke loop



50mm 'O' ring



RIDGEGEAR LIMITED 📍 Nelson Street, Leek, Staffordshire ST13 6BB 📞 Telephone: +44 (0)1538 384 108 ✉ Email: sales@ridgegear.com 🌐 ridgegear.com