



Green Pin® Dee Shackle NS9415 FP




Dee shackle with square sunken hole screw pin (flush) and double safety plug



- **Material:** bow and pin high tensile steel, grade 6, quenched and tempered
- **Safety Factor:** MBL equals 7 x WLL
- **Standard:** NYTEK regulation and NS 9415, ISO 2415, EN 13889, ASME B30.26
- **Finish:** hot dipped galvanized
- **Certification:** 2.1 2.2 3.1 MTC⁹ CE IIA DNV NS 9415
- **Article code:** scan QR code to see article codes
- **Note:** key for unscrewing the pin and safety plug must be ordered separately



G-4139



working load limit	diameter bow	diameter pin	diameter eye	width eye	width inside	length inside	length	length bolt	size square hole	diameter plug hole	depth plug hole	weight each
t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	k mm	kg
2	13.5	16	34	13	22	43	81	51	11	8	8	0.29
3.25	16	19	40	16	27	51	97	63	11	8	8	0.60
4.75	19	22	46	19	31	59	112	74	11	8	8	0.98
6.5	22	25	52	22	36	73	134	85	13	8	8	1.26
8.5	25	28	59	25	43	85	154	99	13	8	8	2.14

CAD

