




# Green Pin® Fishing Dee Shackle FP

## Dee shackle with square sunken hole screw pin (flush pin)



- **Material:** bow and pin high tensile steel, grade 6, quenched and tempered
- **Safety Factor:** MBL equals 6 x WLL
- **Standard:** ISO 2415, EN 13889, ASME B30.26 and meets performance requirements of US Fed. Spec. RR-C-271, grade A
- **Finish:** hot dipped galvanized
- **Certification:** 2.1 2.2 3.1 MTC<sup>3</sup> CE IIA
- **Article code:** scan QR code to see article codes
- **Note:** key for unscrewing the pin must be ordered separately

G-4159



working load limit	diameter bow	diameter pin	diameter eye	width eye	width inside	length inside	length	length bolt	size hole head	weight each
t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	kg
2	13.5	16	34	13	22	43	82	51	11	0.29
3.25	16	19	40	16	27	51	97	63	11	0.60
4.75	19	22	46	19	31	59	112	74	11	0.98
6.5	22	25	52	22	36	73	134	85	13	1.26
8.5	25	28	59	25	43	85	154	99	13	2.14
9.5	28	32	67	28	47	90	168	110	17	2.58
12	32	35	73	32	51	94	180	122	17	3.49
17	38	42	88	38	60	127	230	145	17	6.22

