

Scan for additional product details




Green Pin® Fishing Bow Shackle FP

Bow shackle with square sunken hole screw pin (flush pin)



G-4169



- **Material:** bow and pin high tensile steel, grade 6, quenched and tempered
- **Safety Factor:** MBL equals 6 x WLL
- **Standard:** ISO 2415, EN 13889, ASME B30.26 and meets performance requirements of US Fed. Spec. RR-C-271, grade A hot dipped galvanized
- **Finish:**
- **Certification:** 2.1 2.2 3.1 MTC³ CE IIA
- **Article code:** scan QR code to see article codes
- **Note:** key for unscrewing the pin must be ordered separately

working load limit	diameter bow	diameter pin	diameter eye	width eye	width inside	length inside	width bow	length	length bolt	width	size hole head	weight each
t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	k mm	kg
2	13.5	16	34	13	22	51	32	89	51	59	11	0.31
3.25	16	19	40	16	27	64	43	110	63	75	11	0.56
4.75	19	22	46	19	31	76	51	129	74	89	11	0.96
6.5	22	25	52	22	36	83	58	144	85	102	13	1.46
8.5	25	28	59	25	43	95	68	164	99	118	13	2.18
9.5	28	32	67	28	47	108	75	185	110	131	17	2.84
12	32	35	73	32	51	115	83	201	122	147	17	3.91
17	38	42	88	38	60	146	99	249	145	175	17	6.81

