




Green Pin® Mooring Bow Shackle NS9415 BN


Grade 8 mooring bow shackle with safety bolt and sunken bolt head

Scan for additional product details



- **Material:** bow and pin alloy steel, grade 8, quenched and tempered
- **Standard:** NYTEK regulation and NS 9415
- **Finish:** hot dipped galvanized
- **Temperature Range:** -20 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC[®] CE IIA DNV NS 9415
- **Article code:** scan QR code to see article codes
- **Note:** the synthetic cotter pin is available for sizes MBL 30 t up to 90 t and must be ordered separately

G-4863



minimum breaking load	diameter bow	diameter pin	diameter eye	width eye	width inside	length inside	width bow	length	length bolt	width	thickness nut	weight each
t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	k mm	kg
30	19	22	48	19	44	100	58	154	125	96	19	1.34
40	22	25	54	22	52	125	68	187	142	112	22	2.08
60	28	32	66	28	62	150	89	227	178	145	27	4.07
90	32	35	76	32	82	170	98	258	207	162	30	5.95
110	42	45	90	42	112	200	150	310	261	234	25	14.7
150	45	50	105	45	125	225	175	348	288	265	23	16.7

CAD INFO

